



BX-MSR-102 Organic silicone Resin

I. Product Description

Basic Features:

The product is high temperature resistance, electrical insulation, moisture-proof and water-proof. It is an ideal adhesive for high temperature hard mica board and glass fiber cloth laminate sheet. It also can be used as wear-resisting treatment agent and polishing treatment agent for marble and flooring tile. The product has the features of brittle hardness, high curing degree and releases less volatilization in curing process.

II. Technical Specifications

Item	Index
Appearance	Colorless to light yellow liquid, no mechanical impurity
Solid content, %	50 ± 1
Gel time (200°C) min	10-30
Viscosity(4#cup, 25°C, S)	11~20

Note: The above data are for reference only and are not guaranteed technical specifications.

III. Packaging and Storage:

This product is packed in 200kg iron drum, stored in a cool and dry place, avoid direct sunligh, avoid acid and alkali contact. Storied and transported as dangerous goods.

IV. Instructions:

1. The diluent used in this product should not contain water, acid, alkali, amine and other compounds, otherwise it will affect adhesion, dryness and other properties of paint film.
2. This product contains toluene and other flammable and explosive solvents. Attention should be paid to enhancing site ventilation during processing. Pay attention to fire prevention, anti-static, strictly cut off fire sources. Operators should pay attention to labor protection.
3. This product can be diluted with ketones, esters, toluene, xylene, etc.. The shelf life is half a year.